

Keystone Jack

90-Degree

UTP 90-Degree. T568A/B, 110 IDC

CAT-6



SC-CAT6J (White)



SC-CAT6J-BK (Black)



SC-CAT6J-BL (Blue)



SC-CAT6J-GN (Green)



SC-CAT6J-RD (Red)



SC-CAT6J-YL (Yellow)

I. Product Description

Category 6 UTP Keystone Jack

II. Features

1. Dual 568A/B wiring Label
2. Krone/ 110 Universal IDC
3. Optional Dust Cover for protection of socket from dust
4. UL/cUL listed
5. Applicable specifications:
ANSI/TIA/EIA-568-B.2-1
ISO/IEC 11801 2nd edition: 2002
EN50173-1: 2002
FCC Part 68

III. Electrical Specification

1. Insulation Resistance: $\geq 500 \text{ M}$
2. Dielectric Withstand Volt: 1000V
3. Contact Resistance $\leq 20 \text{ M}$
4. Current Rating: 1.5A at 68°F

IV. Mechanical Specification

1. Plug insertion Life: ≥ 750 times plug in
2. Contact Force 99.2g (3.5oz) FCC Plug
3. Plug Retention Force: 30lb (133n/13.3Kg)
4. 110 Jack Insertion Force: 4.5Kg minimum
5. 110 Retention Force: 0.5Kg minimum
6. Temperature Test: -40 to 150°F (-40 to 66°C)
7. Contact Plating: 50u" over contact area

SYN(ONNECT™ Category 6 UTP Keystone Jack

